

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 354 863 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

22.10.2003 Bulletin 2003/43

---(51) Int Cl.7: **C07C 7/10**

(21) Application number: **03006546.0**

(22) Date of filing: **24.03.2003**

(84) Designated Contracting States:

**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**

Designated Extension States:

AL LT LV MK

(71) Applicant: **Haldor Topsoe A/S**

2800 Kgs. Lyngby (DK)

(72) Inventor: **Hommeltott, Sven Ivar**

3400 Hillerod (DK)

(30) Priority: **18.04.2002 DK 200200578**

(54) **Continuous process for the removal of water from a hydrocarbon stream**

(57) Process for the continuous drying of a hydrocarbon stream at a temperature being effective in drying the stream with an ionic liquid drying agent comprising a salt of sulphuric acid being in liquid or melted form at the drying temperature.

EP 1 354 863 A1

EP 1 354 863 A1

(continued)

1. Contact Column (Hydrocarbon drying)	
Ionic liquid flow, g/h	325
Before treatment Wet hydrocarbon feed, ppm water	80
After treatment (product) Dry hydrocarbon product, ppm water	8
Hydrocarbon feed temperature °C	20
Ionic liquid feed temperature °C	20
Hydrocarbon/Ionic liquid rate	0.9

2. Stripping column (Ionic liquid drying)	
Ionic liquid flow, g/h	325
Heptane flow, g/h	approximately 500
Ionic liquid feed temperature °C	(preheated to approximately 100°C)
Heptane feed temperature °C	98

Example 2

[0009] This experiment was performed in the same equipment as used in Example 1 but instead of diethylmethylammonium bisulphate, $\text{Et}_2\text{MeNH}^+\text{HSO}_4^-$, a mixture of 164 g $\text{Et}_2\text{MeNH}^+\text{HSO}_4^-$ and 83 g 96% H_2SO_4 (1:1 molar ratio) was used.

1. Contact Column	
Hydrocarbon flow (feed), g/h	514
Ionic liquid flow, g/h	325
Before treatment Wet hydrocarbon feed, ppm water	49
After treatment (product) Dry hydrocarbon product, ppm water	7
Hydrocarbon feed temperature °C	20
Ionic liquid feed temperature °C	20
Hydrocarbon/Ionic liquid rate	1.6

2. Stripping column	
Ionic liquid flow, g/h	409
Heptane flow, g/h	Approximately 500
Before treatment Wet ionic liquid, ppm water	104
After treatment Dry ionic liquid, ppm water	66
Ionic liquid feed temperature °C	(Preheated to approximately 100°C)
Stripping temperature °C	175



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 00 6546

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	US 4 484 933 A (COHEN ALAN P) 27 November 1984 (1984-11-27) -----		C07C7/10
A	US 3 793 187 A (MARX H ET AL) 19 February 1974 (1974-02-19) -----		
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			C07C
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 2 July 2003	Examiner Van Geyt, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03/02 (P04001)